

NKS 30 80/200

NKS Air Duct 30 mm - Outdoor · NKS 30 80/200

0.022

W/mK thermal conductivity

20 - 40

mm core thickness

1200

mm cover width

2400

mm maximum length

PRODUCT DESCRIPTION

NKS 30 80/200 is a board produced for ventilation ducts running outdoors. The numbers indicate the aluminium thickness on the two faces: the aluminium on the outer face is noticeably thicker.



TECHNICAL PROPERTIES

Core material	PIR
Fire class	B-s1-d0
Thermal conductivity	0.022 W/mK
Core thicknesses	20 mm · 40 mm
Facing options	Lack (Opsiyonel)
Company certificates	ISO 9001 · ISO 14001 · ISO 45001 · TSE · YMB · CE

DIMENSIONS

DESIGN	COVER WIDTH	THICKNESS	MAXIMUM LENGTH
Stucco Embos	1200 mm	20 - 40 mm	2400 mm

CORE MATERIAL

TS EN 14509 · TS EN 12667 · TS EN 13501-1

MATERIAL	DENSITY	THICKNESS	THERMAL CONDUCTIVITY	FIRE CLASS
PIR	48-52 kg/m ³ PIR	20 - 40 mm	0.022 W/mK	B-s1-d0

FOR INFORMATIONwww.nuhpanel.com.tr

+90 262 751 07 79

This technical data sheet has been prepared according to the current technical information and standards of Nuhpanel Yapı Elemanları Sanayi Ticaret A.Ş. (Gebze, Kocaeli). The right to make technical changes is reserved.



Product page