

PIRBOARD AL

PIRBOARD Alu / Alu · PIRBOARD AL

0.022

W/mK thermal conductivity

20 - 200

mm core thickness

1200

mm cover width

2400

mm maximum length

PRODUCT DESCRIPTION

PIRBOARD AL is a PIR insulation board faced with aluminium foil on both sides. The foil acts as a vapour barrier and also reduces radiant heat transfer.



TECHNICAL PROPERTIES

Core material	PIR
Fire class	B-s1-d0
Thermal conductivity	0.022 W/mK
Core thicknesses	20 mm · 30 mm · 40 mm · 50 mm · 60 mm · 70 mm · 80 mm · 100 mm · 150 mm · 200 mm
Company certificates	ISO 9001 · ISO 14001 · ISO 45001 · TSE · YMB · CE

DIMENSIONS

COVER WIDTH	THICKNESS	MAXIMUM LENGTH
1200 mm	20 - 200 mm	2400 mm

CORE MATERIAL

TS EN 14509 · TS EN 12667 · TS EN 13501-1

MATERIAL	DENSITY	THICKNESS	THERMAL CONDUCTIVITY	FIRE CLASS
PIR	33-40 kg/m ³ PIR	20 - 200 mm	0.022 W/mK	B-s1-d0

FOR INFORMATIONwww.nuhpanel.com.tr

+90 262 751 07 79

This technical data sheet has been prepared according to the current technical information and standards of Nuhpanel Yapı Elemanları Sanayi Ticaret A.Ş. (Gebze, Kocaeli). The right to make technical changes is reserved.



Product page